

USB Gen1 Type-C Triple Display Dynamic PD Charging Dock with 100 Watt Power Supply



Product Name:

USB Gen1 Type-C Triple Display Dynamic PD Charging Dock with 100 Watt Power Supply

Product Series: Docking Station

Product Code: CSV-1564W100

EAN code: 8719214471866

UPC code: 841615101849

Description:

The Club 3D CSV-1564W100 USB Gen1 Type-C Triple Display Dynamic PD Charging Dock is an integrated solution combining Video, Data, Power, Ethernet and Audio especially for frequent travellers. The Three different Video ports(HDMI™, DisplayPort™, VGA) allow you to enjoy 3 different images or videos on 3 different displays simultaneously under MST mode. The USB Type-A ports and USB Type-C data port allow you to connect multiple USB devices to the host. The USB Type-C charging port allows you to provide power for this Dock and can charge the host PC at the same time by connecting a PD power Adapter, no need to carry your Notebooks PowerSupply. So in general the user is travelling lighter. The Micro SD and SD/MMC ports allow you to read information in the memory card onto the host. The 3.5mm audio port allows enjoying music of the host via a headset. Besides, with the Gigabit Ethernet port, you can enjoy high speed Ethernet on the host. It supports all DP Alt mode supported hosts. (PC, Laptop, Mobile phone, etc.) Dynamic Current Detection and Power Distribution, the product no longer intercepts the fixed power from the external PD Power Supply, but intercepts it according to the actual power consumed by itself, so that the PC can be dynamically charged more power. For Video Signal the source device needs to support DisplayPort™ Alt Mode.

Features:

- Supports DP Alt Mode and PD 3.0
- Supports max. 5Gbps data transmission on the USB Gen1 Type-C ports
- One USB Gen1 Type-C Data port
- One USB Gen1 Type-C port supports PD charging with max100W(20V/5A) Bundled with 100W Power Supply
- HDMI™ max 4K30Hz
- DP™ max 4K30Hz
- VGA max 1920x1200 60Hz
- Triple Display support
- One port IEEE 802.3 Ethernet support for up to 1000BASE-TX
- SD- and Micro-SD Slots work simultaneously
- Audio port(Stereo), supports both micro- and head-phone
- Supports Dynamic Current Detection and Power Distribution, the product no longer intercepts the fixed power from the external PD PowerSupply, but intercepts it according to the actual power consumed by itself, so that the PC can be dynamically charged more power.

- The resolution may degrade to lower version when 2 or 3 videos are connected due to bandwidth limitation
- Support three videos to display simultaneously with the same picture under SST mode
- Support three different videos to display simultaneously under MST mode

Important note for Apple M1-chip based computers:

Please note that for Mac Systems based on M1 Architecture the Multi Display function of Thunderbolt 3 is not enabled. This product will not work with the M1 Architecture.

* Please update your TV Firmware to the version which supports these resolutions/refresh rates!

** Please update your Graphic drivers on your PC and make sure that DSC1.2 is supported on your devices to support the these resolutions/refresh rates!

Please use one of our Extension/Adapter cables to connect to your devices: In case you need assistance to choose the correct cable, please visit our website www.club-3d.com or feel free to mail us at support@club-3d.com and it will be our pleasure to assist you.



OS Support:

- Microsoft Windows® 10
- Mac OS X® Supports SST mode Only

In the box:

- CSV-1564W100 Docking Station
- PowerSupply 100 Watt
- 2x USB Type C cable: 1x connection to Host 27cm / 0.886ft, 1x RED cable USB type C for charging to PowerSupply 1 m / 3.28 ft
- Quick Install Guide

Available Interfaces

Input:

- USB Gen1 Type-C Female for connecting to Host

Output:

- 2x USB Gen1 Type-C Female (1-for Data, 1 for PD charging)
- 3x USB Gen1 Type-A female
- 2x USB 2.0 Type-A female
- 1x HDMI™ female
- 1x DisplayPort™ female
- 1x VGA female
- 1x RJ45 jack
- 1x SD slot
- 1x Micro SD slot
- 1x 3.5mm Stereo jack (Headphone/Mic)

Other info:

- Box size: 36.7 x 7.9 x 10.9 cm / 14.45 x 3.1 x 4.29"
- Device size: 35 x 7.5 x 2 cm / 13.78 x 2.95 x 0.79"
- Device Weight: depending on power plug ≈ 250 gr. / 8.82 oz.
- USB C cable Weight: 35 gr. / 1.2 oz.
- Box Weight: 239 gr. / 8.43 oz.
- Powersupply weight: depending on power plug ≈ 425 gr. / 14.99 oz.
- Total Weight: depending on power plug ≈ 949 gr. / 33.425 oz.
- Meets ROHS, FCC, and CE EMI requirements

Warning Safe Usage: Only to be used at altitude 2000 meters/6562 feet and below.

Input:



USB Type-C



Disclaimer: While we endeavour to provide the most accurate, up-to-date information available, the content on this document may be out of date or include omissions, inaccuracies or other errors. Products might obtain a certification during their lifetime. This doesn't change or alter the product specifications and/or performance in any way. Club 3D will provide the updated information on their website www.club-3d.com at her discretion. Therefore Club 3D does not accept any rights claimed on the content of this document. Please refer to a full overview of our Legacy Terms and Conditions on www.club-3d.com. All other brand names are trademarks or registered trademarks and are the property of their respective owners. All content is subject to change without prior notice.